



PRODUCT DATA SHEET

4353

HYDRAULIC OIL HMZF 32

Date: 03.03.2020

Specification:

DIN 51524/2 HLP, ISO 11158 HM, AFNOR NFE 48-603 HM, Eaton (Vickers), M-2950-S/I-286-S

Product Description:

HYDRAULIC OIL HMZF 32 is a premium quality zinc free anti wear hydraulic oil developed for use in high pressure hydraulic systems operating under varying temperatures where small viscosity changes with fluctuating temperatures are preferred.

HYDRAULIC OIL HMZF 32 oil is formulated with carefully selected base stocks fortified with additives and a very shear stable viscosity in dex improver to impart excellent protection towards wear, rust and oxidation. The viscosity improver reduces the viscosity decrease with rising temperatures.

HYDRAULIC OIL HMZF 32 is formulated with field proven thermally stable, zinc free.

HYDRAULIC OIL HMZF 32 provides excellent water demulsibility as well as de-aeration and effectively protects against rust and oxidation.

HYDRAULIC OIL HMZF 32 can be used in hydraulic systems in stationary and mobile hydraulic systems, as well as for general machine lubrication.

PROPERTY	TEST METHOD	TYPICAL VALUE
ISO Viscosity Grade	ISO 3448	32
Density @ 15° C	ASTM D4052	871 kg/m ³
Kinematic Viscosity @40° C	ASTM D7042	28.5-35.2 mm ² /s
Flash Point (COC)	ASTM D92	>195°C
Pour Point	ASTM D97	-18°C

www.gasoline-oil.com