PRODUCT DATA SHEET 4332

UNIVERSAL TRACTOR OIL SYN 80W

Date: 03.03.2020

Specification: API GL4, NH MAT 3525/3526, JD J20C/20D, Volvo WB 101, MF 1145, CASE MS 1204/6/7/9, NH MAT 3540 (CVT), AGCO CVT ML200, Valtra G2-08(XT-60), Claas CVT, Fendt Vario ZF TE-ML-06B/D/E/F/H/M

UNIVERSAL TRACTOR OIL SYN 80W is a high performance fluid for use in (CVT) transmissions, hydraulic systems, oil immersed brakes of tractors and off-road equipment. These fluids are specially designed for use where a common lubricant reservoir serves transmissions, final drives and hydraulic systems and to optimize the performance of agricultural and commercial tractors.
UNIVERSAL TRACTOR OIL SYN 80W is based on high quality synthetic base oil in combination with an unique additive package to ensure the following properties:

- **High oil aging resistance due to its synthetic base oils, allowing high drain intervals.**
- **Enhanced frictional properties optimize clutch performance and ensure noise free operation of wet brakes.**
- **High viscosity index coupled with high shear stability provides consistent performance.**
- **Excellent low temperature fluidity provides good response and effective lubrication at low ambient temperatures.**
- **Robust anti-wear and extreme pressure properties control wear, extend equipment life and reduce maintenance costs.**
- **Multipurpose capability reduces inventory and prevents accidental contamination and misapplication.**

PROPERTY	TEST METHOD	TYPICAL VALUE
SAE Grade	SAE J300	80W
Density @ 15° C	ASTM D4052	859 kg/m³
Kinematic Viscosity @ 40° C	ASTM D7042	51.1 mm²/s
Flash Point (COC)	ASTM D92	>201°C
Pour Point	ASTM D97	-42°C

www.gasoline-oil.com

Gasoline Oil Company GmbH - Erwin Greiner Strasse 5D - 4690 Rüstorf – Austria – mail: office@gasoline-oil.com