



## PRODUCT DATA SHEET

**4368**

### **SLIDEWAY OIL 68**

Date: 03.03.2020

**Specification:**

ISO 19378-L-GA/GB, DIN 51502: CGLP, AFNOR E 60-203 L-G, GM: LS-2: LW-06-1-04, Medium MAG Industrial Automation Systems, LLC (bekannt als Cincinnati Machine): P-47

**Product Description:**

SLIDEWAY OIL 68 is specially formulated for the lubrication of slide ways on machine tools.

SLIDEWAY OIL 68 is formulated with special additives to impart tackiness and adhesiveness.

SLIDEWAY OIL 68 overcomes stick-slip motion associated with slow moving parts.

SLIDEWAY OIL 68 can be used on all horizontal and vertical slide ways where a good quality lubricant is required for protection of the slide ways.

SLIDEWAY OIL 68 has good demulsifying properties and protects slide ways against staining and corrosion.

PROPERTY	TEST METHOD	TYPICAL VALUE
ISO Viscosity Grade	ISO 3448	68
Density @ 15° C	ASTM D4052	885 kg/m <sup>3</sup>
Kinematic Viscosity @ 100° C	ASTM D7042	8.7 mm <sup>2</sup> /s
Flash Point (COC)	ASTM D92	180°C
Pour Point	ASTM D97	-15°C

***[www.gasoline-oil.com](http://www.gasoline-oil.com)***